

Quench Wash

Industrial Spray Cleaner

Quench Wash is a concentrated liquid alkaline spray cleaner designed to safely remove Quench Oils prior to tempering in the Heat Treatment Department.

Quench Wash provides excellent cleaning and temporary rust protection on ferrous metals and is nonspotting.

Quench Wash is low foaming and splits free oils for more effective skimming or coalescing. This will extend bath life and reduce waste and maintenance.

Quench Wash does not contain phosphates, nitrites, or MEA and can be used in all in-process cleaning systems.

Uses:

Spray Washers

Use at 2 to 5% by volume depending on soils and frequency of application with an operating temperature range of 80° to 180°F.

Power Washers

Use at 1 to 4% by volume depending on soils and frequency of application with an operating temperature range of 80° to 180°F.

Physical Properties

Appearance	Clear liquid	Odor	Mild
Biodegradable	Yes	pH @ 1%	~10.5
Specific Gravity	1.02	Flash Point	None
Emulsification	Rapid	Wetting Ability	Excellent
Foaming	Controlled/Low	Rinsing	Excellent

Environmental

No health or safety hazards exist when Quench Wash is used, stored, and disposed of in accordance with instructions on the Material Safety Data Sheet for this product.

Precision Finishing Inc.

1800 AM Drive, Quakertown, PA 18951
 Phone: (800) 523-6232 / Fax: (215) 257-4162
 E-mail: info@chemtrolcompounds.com