

# CHEMTROL 534

CHEMTROL 534 IS A CONCENTRATED HIGH CAUSTIC CLEANER FOR USE IN IMMERSION APPLICATIONS FOR PROCESSING FERROUS METALS. ESPECIALLY DESIGNED FOR HOT TANK CLEANING DURING OVERHAUL AND REBUILDING.

## KEY PERFORMANCE BENEFITS:

EXCELLENT FOR THE REMOVAL OF CARBON, RUST, HEAVY OILS AND GREASES, GUMS, ADHESIVES, AND MOST TYPES OF PAINT.

EFFECTIVE AT LOW CONCENTRATION.

MEDIUM FOAMING IN MOST APPLICATIONS.

## SPECIFICATIONS:

APPEARANCE	FREE FLOWING TAN POWDER
PH 1% SOLUTION	12.9
SPECIFIC GRAVITY	2.0
PHOSPHATE FREE	NO
FOAMING TENDENCY	MEDIUM TO HIGH

## CAUTION...

CHEMTROL 534 IS A CORROSIVE PRODUCT WHICH CAUSES BURNS TO THE SKIN, EYES, AND MUCOUS MEMBRANES.  
CONSULT MSDS BEFORE HANDLING.  
AVOID CONTACT WITH SKIN, EYES, OR CLOTHING.

## FIRST AID...

IN CASE OF CONTACT, WASH AFFECTED AREA WITH WATER.  
FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES.  
IF IRRITATION PERSISTS, SEEK PROMPT MEDICAL ATTENTION.

## WASTE DISPOSAL...

ADJUST PH TO MEET LOCAL CODES. DOES NOT CONTAIN HEAVY METALS.